

## PRODUCT DATA SHEET

### Medium Stuff

<b>Description</b>	A chalk lime putty based mortar/plaster with a blend of sands and grit.
<b>1. Colour code</b>	BL31 Chalk white
<b>Aggregate blend</b>	2.5 parts Wareham washed, 0.5 parts Playpit sand
<b>2. Colour code</b>	LS1 Oatmeal
<b>Aggregate blend</b>	1 part Frith end blend, 2 parts Wareham washed
<b>Lime Putty</b>	Singleton Birch chalk lime putty matured min 1 month
<b>Aggregate size</b>	<4mm
<b>Mix ratio</b>	1:3 lime/sand
<b>Uses</b>	As an internal or external base coat.
<b>Approximate Coverage</b>	1m <sup>2</sup> /25kg at 10mm thickness onto wooden lath. 1.2m <sup>2</sup> /25kg at 10mm thickness onto solid substrate.
<b>Shelf Life</b>	Avoid exposure to excess heat or cold. Lime plaster matures and improves with age when kept sealed.
<b>Units</b>	25kg plastic tub, 25kg plastic bag, 500kg bulk bag, 1000kg bulk bags.
<b>Health and Safety</b>	Contains Calcuim Hydroxide CA(OH) <sup>2</sup> . <b>GHS07</b> Harmful/Irritant/Skin Sensitizer <b>H315</b> Causes skin irritation <b>GHS05</b> Corrosive <b>H318</b> Causes serious eye damage <b>Precautionary Statements</b> <b>P102</b> Keep out of reach of children <b>P262</b> Do not get in eyes, on skin, or on clothing <b>P280</b> Wear protective gloves/protective clothing/eye protection/face protection <b>P305+P310+P351</b> If in eyes rinse continuously with water for several minutes and immediately seek medical assistance <b>P302+P352</b> If on skin wash with plenty of soap and water
<b>Observations</b>	Recommended to be used by professional tradesmen experienced in the application of lime plasters.
<b>Technical Advice</b>	Call 01794 884294 or email info@limestuff.co.uk