

PRODUCT DATA SHEET

Coarse Stuff

Description	A chalk lime putty based mortar/plaster with a blend of sands and grit.
1. Colour code	BL40 Chalk white
Aggregate blend	2 parts Wareham washed sharp sand, 1 part Newbury Grit sand,
2. Colour code	LS2 Oatmeal
Aggregate blend	1 part Frith End Blend, 1 part Wareham washed sharp sand, 1 part Newbury Grit sand.
Lime Putty	Singleton Birch chalk lime putty matured min 1 month
Aggregate size	<4mm
Mix ratio	1:3 lime/sand
Uses	As an internal or external base coat.
Approximate Coverage	1m ² /25kg at 10mm thickness onto wooden lath. 1.2m ² /25kg at 10mm thickness onto solid substrate.
Shelf Life	Avoid exposure to excess heat or cold. Lime plaster matures and improves with age when kept sealed.
Units	25kg plastic tub, 25kg plastic bag, 500kg bulk bag, 1000kg bulk bags.
Health and Safety	Contains Calcium Hydroxide CA(OH) ² . GHS07 Harmful/Irritant/Skin Sensitizer H315 Causes skin irritation GHS05 Corrosive H318 Causes serious eye damage Precautionary Statements P102 Keep out of reach of children P262 Do not get in eyes, on skin, or on clothing P280 Wear protective gloves/protective clothing/eye protection/face protection P305+P310+P351 If in eyes rinse continuously with water for several minutes and immediately seek medical assistance P302+P352 If on skin wash with plenty of soap and water
Observations	Recommended to be used by professional tradesmen experienced in the application of lime plasters.
Technical Advice	Call 01794 884294 or email info@limestuff.co.uk